



SAFETY DATA SHEET

PROFIN® GLOSS/REGULAR

Revised Date: 09-16-2015

Supersedes: 01-10-2001

1. Identification

Product identifier	ProFin® Gloss/Regular
Other means of identification	
SDS number	09
Synonyms	15560
Recommended use	Not available.
Recommended restrictions	Not available.
Manufacturer/Importer/Supplier/Distributor information	
Manufacturer/Supplier	Daly's Wood Finishing Products, 4522 S 133 rd St , Tukwila, WA 98168. (206) 244-8844, toll free: (800) 727-9694 info@dalyswoodfinishes.com
General Assistance	
E-Mail	Not available.
Contact Person	Chemtrec : 800-424-9300
Emergency Telephone	

2. Hazard(s) Identification

Physical hazards	Flammable liquids	Category 3
Health hazards	Skin corrosion/irritation	Category 2
	Carcinogenicity	Category 2
	Reproductive toxicity	Category 2
	Specific target organ toxicity, single exposure; Narcotic effects, Aspiration hazard	Category 3
		Category 1

Label elements



Signal word

Danger

Unknown Toxicity

54.06 % of the mixture consists of ingredient(s) of unknown toxicity.

Hazard statement

Flammable liquid and vapor. Causes skin irritation. Suspected of causing cancer. Suspected of damaging fertility or the unborn child. May cause drowsiness or dizziness. May be fatal if swallowed and enter the airways.

Precautionary statement

Prevention

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container tightly closed. Ground and bond container and receiving equipment.



SAFETY DATA SHEET

PROFIN® GLOSS/REGULAR

Revised Date: 09-16-2015

Supersedes: 01-10-2001

Response

Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take action to prevent static discharges. Wear protective gloves/protective clothing/eye protection/face protection. Wash skin thoroughly after handling. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid breathing dust/fume/gas/mist/vapors/spray. Use only outdoors or in a well-ventilated area.

IF ON SKIN (or hair): Take off Immediately all contaminated clothing. Rinse SKIN with water/shower. In case of fire: Use CO₂, dry chemical, foam, water fog for extinction. IF ON SKIN: wash with plenty of soap and water. IF SKIN irritation occurs: Get medical advice/attention. IF INHALED: Remove person to fresh air and Keep comfortable for breathing. IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting.

Storage

Store locked up. Store in a well-ventilated place. Keep cool. Keep container tightly closed.

Disposal

Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise classified (HNOC)

None known.

3. Composition/information on ingredients

Mixture

<u>Chemical name</u>	<u>CAS number</u>	<u>%</u>
Mineral spirits	64742-47-8	40
Xylene	1330-20-7	<5
Ethylbenzene	100-41-4	
Stoddard solvent (< 0.1% Benzene)	8052-41-3	0.3
2-Ethylhexanoic acid	149-57-5	
n-Butanol	71-36-3	
1,10-Phenanthroline	66-71-7	

4. First-aid measures

Inhalation

Move individual to fresh air. If breathing has stopped, apply artificial respiration, get medical attention immediately.

Skin contact

Wash off quickly with plenty of water, then soap and water. Remove and wash contaminated clothing before reuse.

Eye contact

Wash with clean water for at least fifteen minutes; get medical



Revised Date: 09-16-2015

SAFETY DATA SHEET

PROFIN® GLOSS/REGULAR

Supersedes: 01-10-2001

Ingestion	attention. DO NOT INDUCE VOMITING. Give water or milk to drink; get medical attention.
Most important symptoms/effects, acute and delayed	May cause redness, irritation of eye. Inhalation may cause dizziness, headache, nausea, possible nervous system depression. Ingestion may cause nausea, gastrointestinal irritation, or vomiting. When comes in contact with skin may cause rash, cracking, dryness or defatting of skin. Pre-existing lung or skin conditions could be aggravated by repeated exposure.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed. In case of shortness of breath, give oxygen. Keep victim warm.
General information	If exposed or concerned: get medical attention/advice. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before re-use.

5. Fire-fighting measures

Suitable extinguishing media	CO ₂ , dry chemical, foam, water spray.
Unsuitable extinguishing media	None known.
Specific hazards arising from the chemical	None known.
Special protective equipment and Special firefighting procedures	Fight as a volatile fire; do not enter enclosed or confined fire spaces without proper protective equipment. This may include self-contained breathing apparatus.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Environmental precautions	Avoid discharge into drains, water courses or onto the ground.



SAFETY DATA SHEET

PROFIN® GLOSS/REGULAR

Revised Date: 09-16-2015

Supersedes: 01-10-2001

Methods and materials for containment and cleaning up

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Provide ventilation. Take precautionary measures against static discharge. Avoid dispersal of dust in the air (i.e., clearing dust surfaces with compressed air). Stop the flow of material, if this is without risk. Soak up spill with absorbent material. Rags and absorbent material should be immersed in water. For waste disposal, see section 13 of the SDS.

7. Handling and storage

Precautions for safe handling

Read and observe all precautions on label. Use only with adequate ventilation. Do not breathe mist or vapor. Do not get in eyes, on skin, or on clothing. Wear appropriate personal protective equipment. Observe good industrial hygiene practices. Do not reuse container for other purposes.

Conditions for safe storage

KEEP OUT OF REACH OF CHILDREN. Store locked up. Store in original container; keep tightly closed and appropriately labeled. Do not reuse container for other purposes. Store away from incompatible materials. Store away from high temperature, sparks, or open flame.

Incompatible materials

Avoid strong oxidizing agents.

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Components	Type	Value
Mineral spirits	PEL(TWA)	500 ppm
Xylene	PEL(TWA)	100 ppm (435 mg/m ³)
Ethylbenzene	PEL(TWA)	100 ppm
Stoddard solvent	PEL(TWA)	500 ppm (2900 mg/m ³)
n-Butanol	PEL(TWA)	100 ppm

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value
Mineral spirits	TWA	500 ppm
Xylene	TWA	100 ppm (435 mg/m ³)
Ethylbenzene	TWA	100 ppm
Stoddard solvent	TWA	500 ppm (2900 mg/m ³)
n- Butanol	TWA	100 ppm (300mg/m ³)



SAFETY DATA SHEET

PROFIN® GLOSS/REGULAR

Revised Date: 09-16-2015

Supersedes: 01-10-2001

US. OSHA Table Z-2 (29 CFR 1910.1000)

None of the components in this product is listed.

US. OSHA Table Z-3 (29 CFR 1910.1000)

None of the components in this product is listed.

US. ACGIH Threshold Limit Values

Components	Type	Value
Mineral spirits	TLV (TWA)	100 ppm
Xylene	TLV (TWA)	100 ppm
	TLV (ST)	150 ppm
Ethylbenzene	TLV (TWA)	20 ppm
Stoddard solvent	TLV (TWA)	100 ppm
n-Butanol	TLV (TWA)	20 ppm

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value
Mineral spirits	REL (TWA)	350 mg/m ³
	REL (Ceiling)	1800 mg/m ³ (15-minute)
Silicon dioxide	REL (TWA)	6 mg/m ³
	REL (ST)	150 ppm (655 mg/m ³)
Xylene	REL (TWA)	100 ppm (435 mg/m ³)
	REL (ST)	150 ppm (655 mg/m ³)
Ethylbenzene	REL (TWA)	100 ppm
	REL (ST)	125 ppm
n-Butanol	REL (Ceiling)	50 ppm (150 mg/m ³)

Appropriate engineering controls

Provide adequate general and local exhaust ventilation, especially in confined areas. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Ensure all national/local regulations are observed.

Individual protection measures, such as personal protective equipment

Eye/face protection

Goggles or face shield.

Skin protection

Hand protection

Wear neoprene or rubber gloves.

Other

Wear impervious protective clothing. Eyewash station should be available.

Respiratory protection

Wear a NIOSH approved respirator for organic vapors and ensure workers are trained in proper use. Provide adequate ventilation to keep vapor concentration below TLV.

Thermal hazards

Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Avoid contact with eyes. Avoid contact with skin. Keep away from food and drink. Keep work area clean and free from spills and leaks. Wash hands before breaks and immediately after handling the product. Provide eyewash station and safety shower. Handle in



SAFETY DATA SHEET

PROFIN® GLOSS/REGULAR

Revised Date: 09-16-2015

Supersedes: 01-10-2001

accordance with good industrial hygiene and safety practice.

9. Physical and chemical properties

Appearance	Pale yellow liquid.
Physical state	Liquid.
Form	Liquid.
Color	Pale yellow.
Odor	Petroleum distillate odor.
Odor threshold	Not available.
pH	Not available.
Melting point	Not available.
Freezing point	Not available.
Initial boiling point and boiling range	370-405 °F
Flash point	107 °F
% Volatile by Volume	70 %
Evaporation rate (BuOAc=1)	0.13
Maximum Volatile Organic Compound (V.O.C.)	550 grams/liter
Flammability (solid, liquid, gas)	Flammable liquid and vapors.
Upper/lower flammability or explosive limits	
Flammability limit – lower (%)	Not available.
Flammability limit – upper (%)	Not available.
Explosive limit - lower (%)	1.0
Explosive limit - upper (%)	6.0
Vapor pressure (mm Hg)	5mm Hg at 77 °F
Vapor density (Air=1)	4.9
Relative density (Specific gravity)	0.86
Solubility(ies)	
Solubility (water)	Insoluble.
Solubility (other)	Soluble in petroleum solvents.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	Not available.

10. Stability and reactivity

Reactivity	Hazardous reactions will not occur under normal conditions.
Chemical stability	Stable under recommended handling and storage conditions.
Possibility of hazardous reactions	Hazardous polymerization will not occur.
Conditions to avoid	None known
Incompatible materials	Avoid strong oxidizing agents.
Hazardous decomposition Products	Usual products of combustion: CO, CO ₂ possibly acrolein, and oxides of nitrogen.



SAFETY DATA SHEET

PROFIN® GLOSS/REGULAR

Revised Date: 09-16-2015

Supersedes: 01-10-2001

11. Toxicological information

Information on likely routes of exposure

Ingestion May cause nausea, gastrointestinal irritation or vomiting.
Inhalation May cause dizziness, headache, nausea, possible nervous system depression.
Skin contact May cause rash, cracking, dryness or defatting of skin.
Eye contact May cause redness and severe irritation.

Symptoms related to the physical, chemical and toxicological characteristics May cause redness, irritation of eye. Inhalation may cause dizziness, headache, nausea, possible nervous system depression. Ingestion may cause nausea, gastrointestinal irritation, or vomiting. When comes in contact with skin may cause May cause rash, cracking, dryness or defatting of skin.

Delayed and immediate effects and also chronic effects from short- and long-term exposure No adverse long term affects are known, when used in accordance with safe handling information (see section 8). Pre-existing lung or skin conditions could be aggravated by repeated exposure.

Numerical measures of toxicity

Components	Test	Species	Test Results
Mineral spirits (CAS 64742-47-8)	Oral LD ₅₀	Rat	>5000 mg/kg
	Dermal LD ₅₀	Rabbit	>2000 mg/kg
	Inhalation LC ₅₀	Rat	> 5.28 mg/l, 4h
Silicon dioxide (CAS 7631-86-9)	Oral LD ₅₀	Rat	>5000 mg/kg
	Dermal LD ₅₀	Rabbit	>2000 mg/kg
	Inhalation LC ₅₀	Rat	>0.69 mg/l, 4h
Xylene (CAS 1330-20-7)	Oral LD ₅₀	Rat	4300 mg/kg
	Dermal LD ₅₀	Rabbit	>1700 mg/kg
	Inhalation LC ₅₀	Rat	21.7 mg/l, 4h
Ethylbenzene (CAS 100-41-4)	Oral LD ₅₀	Rat	3500 mg/kg
	Dermal LD ₅₀	Rabbit	17800 mg/kg
	Inhalation LC ₅₀	Rat	9.6 mg/l,4h
Stoddard solvent (CAS 8052-41-3)	Oral LD ₅₀	Rat	>5000 mg/kg
	Dermal LD ₅₀	Rabbit	>3000 mg/kg
	Inhalation LC ₅₀	Rat	> 55500 mg/m ³

Skin corrosion/irritation Causes skin irritation.
Serious eye damage/eye irritation No data available.
Respiratory or skin sensitization
Respiratory sensitization No data available.
Skin sensitization No data available.
Germ cell mutagenicity No data available.
Carcinogenicity Suspected of causing cancer.
IARC Monographs. Overall Evaluation of Carcinogenicity



SAFETY DATA SHEET

PROFIN® GLOSS/REGULAR

Revised Date: 09-16-2015

Supersedes: 01-10-2001

Ethylbenzene	2B "Possibly carcinogenic to humans".
NTP Report on Carcinogen	
Ethylbenzene	Not listed.
U.S OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)	
Ethylbenzene	Not listed.
Reproductive toxicity	Suspected of damaging fertility or the unborn child.
Specific target organ toxicity - single exposure	May cause drowsiness or dizziness.
Specific target organ toxicity - repeated exposure	No data available.
Aspiration hazard	May be fatal if swallowed and enter the airways.

12. Ecological information

Numerical measures of toxicity

Components	Test	Species	Test Results
Mineral spirits (CAS 64742-47-8)	Fish LC ₅₀	Bluegill <i>(Lepomis macrochirus)</i>	2.2 mg/l, 96h
Xylene (CAS 1330-20-7)	Fish LC ₅₀	Fathead minnow <i>(Pimephales promelas)</i>	13.4 mg/l, 96h
		Crustacea EC ₅₀	Water flea <i>(Ceriodaphnia dubia)</i>
	Algae EC ₅₀	Microalga <i>(Selenastrum capricornutum)</i>	4.9 mg/l, 72h
Ethylbenzene (CAS 100-41-4)	Fish LC ₅₀	Rainbow trout <i>(Oncorhynchus mykiss)</i>	4.2 mg/l, 96h
		Crustacea EC ₅₀	Water flea <i>(Daphnia magna)</i>
	Algae EC ₅₀	Microalga <i>(Selenastrum capricornutum)</i>	4.6 mg/l, 72h

Persistence and degradability	No information available.
Bioaccumulative potential	No information available.
Mobility in soil	No information available.
Other adverse effects	No information available.

13. Disposal considerations

Disposal instructions	Dispose in accordance with all applicable federal, state and local regulations. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container; dispose of this material and its container in a safe way.
------------------------------	---



SAFETY DATA SHEET

PROFIN® GLOSS/REGULAR

Revised Date: 09-16-2015

Supersedes: 01-10-2001

Hazardous waste code

US RCRA Hazardous Waste U List : Reference

Xylene (CAS 1330-20-7) U239

n-Butanol (CAS 71-36-3) U031

Contaminated packaging

Since emptied containers may retain product residue, follow label warnings even after container is emptied. Do not reuse container for other purposes.

14. Transport information

DOT

UN number	UN 1263
UN proper shipping name	PAINT RELATED MATERIAL
Transport hazard class(es)	
Class	3
Subsidiary risk	-
Label(s)	3 - Flammable liquid



Packing group III

Environmental hazards
Marine pollutant Yes

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

IATA

UN number	UN 1263
UN proper shipping name	Paint related material
Transport hazard class(es)	
Class	3
Subsidiary risk	-
Label(s)	3 - Flammable liquid



Packing group III
Environmental hazards Yes




SAFETY DATA SHEET

PROFIN® GLOSS/REGULAR

Revised Date: 09-16-2015

Supersedes: 01-10-2001

ERG Code	3L
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
IMDG	
UN number	UN 1263
UN proper shipping name	PAINT RELATED MATERIAL
Transport hazard class(es)	
Class	3
Subsidiary risk	-
Label(s)	3 - Flammable liquid
	
Packing group	III
Environmental hazards	
Marine pollutant	Yes
EmS	F-E, S-D
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	Not available.

15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.
All components are on the U.S. EPA TSCA Inventory List.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

None of the chemicals in this product is regulated.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Mineral spirits (CAS 64742-47-8)	Listed
Silicon dioxide (CAS 7631-86-9)	Listed
Xylene (CAS 1330-20-7)	Listed
Ethylbenzene (CAS 100-41-4)	Listed
Stoddard solvent (CAS 8052-41-3)	Listed
n-Butanol (CAS 71-36-3)	Listed

CERCLA Hazardous Substance List (40 CFR 302.4)

Xylene (CAS 1330-20-7)	Listed
Ethylbenzene (CAS 100-41-4)	Listed
n-Butanol (CAS 71-36-3)	Listed



SAFETY DATA SHEET

PROFIN® GLOSS/REGULAR

Revised Date: 09-16-2015

Supersedes: 01-10-2001

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories	Immediate Hazard	-	Yes
	Delayed Hazard	-	Yes
	Fire Hazard	-	Yes
	Pressure Hazard	-	No
	Reactivity Hazard	-	No

SARA 302/304 Extremely hazardous substance

None of the chemicals in this product is listed.

SARA 311/312 Hazardous chemical Yes

SARA 313 (TRI reporting)

Chemical Name	CAS number	% by wt
Xylene	1330-20-7	<3
Ethylbenzene	100-41-4	

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Ethylbenzene (CAS 100-41-4)

Xylene (CAS 1330-20-7)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

None of the chemicals in this product is listed.

Safe Drinking Water Act (SDWA)

n-Butanol (CAS 71-36-3)

US State regulations

WARNING: This product contains chemicals known to the state of California to cause cancer and birth defects or other reproductive harm.

US. New Jersey Worker and Community Right-to-Know Act

Stoddard solvent (CAS 8052-41-3)

Xylene (CAS 1330-20-7)

Ethylbenzene (CAS 100-41-4)

Stoddard solvent (CAS 8052-41-3)

2-Ethylhexanoic acid (CAS 149-57-5)

n-Butanol (CAS 71-36-3)

US. Pennsylvania Worker and Community Right-to-Know Law

Silicon dioxide (CAS 7631-86-9)

Xylene (CAS 1330-20-7)

Ethylbenzene (CAS 100-41-4)

Stoddard solvent (CAS 8052-41-3)

n-Butanol (CAS 71-36-3)

US. California Proposition 65

US - California Proposition 65 - Carcinogens & Reproductive Toxicity (CRT):

Ethylbenzene (CAS 100-41-4)

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Canada	Domestic Substances List (DSL)	Yes
Canada	Non- Domestic Substances List (NDSL)	Yes



SAFETY DATA SHEET

PROFIN® GLOSS/REGULAR

Revised Date: 09-16-2015

Supersedes: 01-10-2001


Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s).

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date 01-10-2001
Revision date 09-16-2015
Version # 01
NFPA rating



References

ACGIH: Documentation of the Threshold Limit Values and Biological Exposure indices
 ECHA: European Chemicals Agency
 HSDB: Hazardous Substances Data Bank
 IARC: International Agency for Research on Cancer
 NIOSH: The National Institute for Occupational Safety and Health
 NTP: National Toxicology Program
 NLM: Hazardous Substances Data Base
 OECD : Organization for Economic Co-operation and Development
 OSHA: Occupational Safety and Health Administration

Disclaimer

The information, recommendations, and suggestions presented in this SDS are based upon test results and data believed to be reliable. The end user of the product has the responsibility for evaluating the adequacy of the data under the conditions of use, determining the safety, toxicity and suitability of the product under these conditions, and obtaining additional or clarifying information where uncertainty exists. No guarantee expressed or implied is made as to the effects of such use, the results to be obtained, or the safety and toxicity of the product in any specific application. Furthermore, the information herein is not represented as absolutely complete, since it is not practicable to provide all the scientific and study information in the format of this document, plus additional information may be necessary under exceptional conditions of use, or because of applicable laws or government regulations. All materials may present unknown hazards and should be used with caution.