



Wood Finishing Products

BenMatte™

Natural Tung-Oil Finish

Product: 13000

08/05/03

SPECIFICATION SHEET

DESCRIPTION:	Daly's BenMatte™ Natural Tung-Oil Finish penetrates into the wood structure, producing the beauty of an oil rubbed finish with the added protection of synthetic resins. BenMatte is durable and easy to apply, resistant to fading and damage by water, alcohol, scratches and abrasions.
RECOMMENDED USES:	All interior wood surfaces such as cabinets, paneling, millwork, doors and furniture.
RECOMMENDED SYSTEMS:	FOR NATURAL UNSTAINED WOOD: the surface should be clean, dry and smooth. Sand if necessary with 120 sandpaper and remove dust. Apply a liberal coat and allow to set for up to 5 minutes for maximum penetration. While still wet with BenMatte , sand with #400 wet/dry sandpaper until smooth feel is produced. Remove excess with a dry absorbent rag. Allow to dry 4 to 6 hours. A second or third coat is recommended for added protection. The additional coats should be wiped on with a rag, sanding is usually not necessary after the first coat. As many coats as desired may be used. FOR USE AS A FINISH OVER DALY'S WOOD STAINS: First, be sure to allow the stain coat to set and dry well before attempting to apply BenMatte - at least 24 to 48 hours. Second, wipe or brush on a liberal coat of BenMatte , allow to set for about 5 minutes then wipe gently to remove the excess using a light touch while wiping. BE SURE NOT TO SAND THIS COAT. Allow to dry 4 to 6 hours before applying an additional coat. Up to six coats may be added for maximum protection.
COLORS & TINTING:	Tinting BenMatte is not recommended. (<i>See Daly's Wood Stains.</i>) It may not be compatible with some universal pigments. For on-the-job tinting, oil soluble pigments are recommended. Always test first for compatibility and desired effect.
THINNING:	Do not thin.
CLEAN UP:	Paint thinner (Mineral spirits).
SURFACE PREPARATION:	All surfaces to be finished must be free of loose dirt, dust, other contaminants, and must be dry.
APPLICATION:	Brush, roller or wipe on.
COVERAGE:	200 to 400 sq. ft. per gallon depending on surface texture and dryness. Additional coats: 500 to 600 sq. ft. per gallon.
DRY TIME:	4 to 6 hours between coats. 24 to 48 hours ready to use.
MAINTENANCE:	If surface becomes or looks dry, apply BenMatte or Daly's LemOil with a soft rag and wipe dry.
CAUTIONS:	DANGER - CONTAINS PETROLEUM DISTILLATE. VAPOR HARMFUL. MAY AFFECT THE BRAIN OR NERVOUS SYSTEM, CAUSING DIZZINESS, HEADACHE OR NAUSEA. CAUSES EYE, SKIN, NOSE AND THROAT IRRITATION.

CAUTIONS (continued): **Notice:** Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.
PRECAUTIONS: Keep away from heat and flame. Prevent build-up of vapors by opening windows and doors to achieve cross ventilation.
USE ONLY WITH ADEQUATE VENTILATION. Do not breath vapors or spray mist. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness, or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during and after application. Follow respirator manufacturer's directions for respirator use. Avoid contact with eyes, skin and clothing. Wash thoroughly after handling.
First Aid: If swallowed, do not induce vomiting. Call physician immediately. If you experience difficulty in breathing, leave area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention; for skin, wash thoroughly with soap and water.
If spilled, contain spilled materials and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.
KEEP OUT OF REACH OF CHILDREN

SPECIAL INSTRUCTIONS: To avoid spontaneous combustion during temporary storage, soak soiled rags and waste immediately after use in a water-filled, closed, metal container. For disposal guidance of unused materials, contact local hazardous waste program or your local or state government environmental control agency.

VEHICLE TYPE: Tung Oil Modified Resin.
WEIGHT PER GAL: 6.9 lb.
% VOL. SOLIDS: 30
FLASH: 107°F
V.O.C.: Maximum 550 grams per liter

Daly's Wood Finishing Products

3525 Stone Way N, Seattle, WA 98103

phone(206) 633-4200

toll free(800) 735-7019

fax(206)632-2565

S-BenMatte.pm6-p2/2