



Commercial Products

Benite AquaSeal Pre-Stain / Wood Conditioner

Product: 21500

11/28/12

SPECIFICATION SHEET

- DESCRIPTION:** Benite AquaSeal is a clear, penetrating pre-stain sealer and wood conditioner that hardens and protects the wood grain. It does not leave a surface film, is practically odorless and has very little environmental impact. AquaSeal is an excellent pre-stain sealer for most stains, oil or water based. It can also be used to protect wood from weather damage before construction by minimizing water absorption.
- RECOMMENDED USES:** Interior: An excellent pre-conditioner to avoid uneven stain absorption that can result in a spotty or blotchy stain appearance.
Exterior: Prevents wood from taking on moisture until stain or finish can be applied.
- DIRECTIONS:** Interior: Sand wood with 120 grit sandpaper following the grain, remove dust and apply with roller, brush, spray or dip. Allow to dry 2 - 4 hours depending on conditions. Benite AquaSeal will raise the grain of the wood slightly so if staining or finishing over AquaSeal sand lightly with 150 or 220 grit sandpaper to a smooth surface before proceeding to the next step.
Exterior: Apply a full flooding coat and do not stack wood until dry. apply in temperatures from 40 - 90 Degrees F.
- SURFACE PREPARATION:** Surface should be free of dust and moisture.
- APPLICATION:** Brush, roller, spray or most any paint applicator.
- CLEAN UP:** Clean tools and brushes with water and a little soap.
- THINNING:** Thinning is not recommended.
- COVERAGE:** 150 - 250 sq.ft. per gallon, over rough wood surfaces. 400 - 500 sq.ft. per gallon, over smooth wood surfaces.
- DRY TIME:** Benite AquaSeal should be allowed to dry for 2 - 4 hours. Temperature and humidity can affect the dry time so if you have concerns allow longer time before recoat.
- STORAGE:** Benite AquaSeal will remain in good condition in the original unopened container for 1 - 2 years. Always pretest to be sure of desired results.
- V.O.C.:** < 50 g/L
- CAUTIONS:** **USE ONLY WITH ADEQUATE VENTILATION.**
Do not breath vapors or spray mist. Ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness or if air monitoring demonstrates vapor/mist levels are above applicable limits wear an appropriate (NIOSH/MSHA approved) properly fitting respirator during and after application. Do not take internally. Close container after each use.
Avoid Contact with eyes, skin and clothing. Wash thoroughly with soap and water after handling.

WARNING: If you scrape, sand or remove old paint you may release lead dust. LEAD IS TOXIC, EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN; PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD.

FIRST AID: If swallowed, do not induce vomiting. Call physician immediately. If you experience difficulty breathing, leave area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention; for skin contact, wash thoroughly with soap and water.

NOTES: If spilled, contain Benite AquaSeal and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

**KEEP OUT OF REACH OF CHILDREN
READ ALL CAUTIONS PRIOR TO USING**

**KEEP FROM FREEZING
ENVIRONMENTALLY FRIENDLY**

In case of chemical emergency call ChemTel (24 hrs): 1-800-255-3924

Daly's Wood Finishing Products

3525 Stone Way N, Seattle, WA 98103

phone(206) 633-4200

toll free(800) 735-7019

fax(206)632-2565