



## SPECIFICATION SHEET

### Benite™

Product:11010

Wood Conditioner

3/2016

#### DESCRIPTION:

Daly's **Benite** is a deeply penetrating wood conditioner, which becomes an integral part of the wood structure, there by hardening the wood. **Benite** does not leave a surface film, and reduces the possibility of grain raising. **Benite** is practically odorless and colorless, and because it penetrates, it won't crack, chalk, blister or peel.

#### RECOMMENDED USES:

**Benite** can be used as a wood conditioner, however, for exterior siding applications it is recommended to use a lightly pigmented stain such as Daly's EXTERIOR SEMI- TRANSPARENT STAIN. It is an excellent pre-conditioner to avoid "spotty" stained surfaces, and prevents wood from taking on moisture until stain or finish can be applied. For greater protection on exterior surfaces such as doors and furniture, use Daly's SEAFIN TEAK OIL, SEAFIN SUPER SPAR VARNISH or AQUASPAR.

INTERIOR - Sand wood with 120 grit sandpaper, remove dust, apply with roller, brush, spray or dip. Allow to dry. Sand with 150 or 220 grit sandpaper before staining or finishing over Benite.

EXTERIOR - Apply a full flooding coat. Do not stack treated wood until dry.

**THINNING:** Not recommended. Product is ready to use as packaged.

**CLEAN UP:** Paint thinner (Mineral spirits).

**APPLICATION:** Brush, roller, spray or most any applicator.

**SURFACE PREPARATION:** Surface should be free of dust and moisture.

#### COVERAGE:

150 to 200 square feet per gallon on rough surfaces, and 400 to 500 square feet per gallon over smooth wood surfaces.

**DRY TIME:** Allow 12-24 hours dry time. Temperature and humidity can affect dry time.

#### CAUTIONS:

**CONTAINS PETROLEUM DISTILLATE:** VAPOR HARMFUL. MAY AFFECT THE BRAIN OR NERVOUS SYSTEM CAUSING DIZZINESS, HEADACHE OR NAUSEA. CAUSES EYE, SKIN, NOSE AND THROAT IRRITATION. Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

**PRECAUTIONS:** Keep away from heat and flame. Prevent build-up of vapors by opening windows and doors to achieve cross ventilation.

USE ONLY WITH ADEQUATE VENTILATION.

**CAUTIONS CONTINUED:**

USE ONLY WITH ADEQUATE VENTILATION. Do not breathe vapors or spray mist. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness, or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during and after application. Follow respirator manufacturer's directions for respirator use. Avoid contact with eyes, skin and clothing. Wash thoroughly after handling. Close container after each use.

**Warning:** Rags and other waste materials soiled with this product may spontaneously catch fire if improperly discarded. Soak soiled rags and waste immediately after use in a water-filled, closed metal container. For disposal guidance of unused materials, contact a house hold hazardous waste program or your local or state government environmental control agency.

**First Aid:** If swallowed, do not induce vomiting. Call physician immediately. If you experience difficulty breathing, leave area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention. For skin contact, wash thoroughly with soap and water.

**SPECIAL INSTRUCTIONS:**

**IF SPILLED:** Contain spilled materials and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

**DISPOSAL OF OILY RAGS:** To avoid spontaneous combustion during temporary storage, soak soiled rags and waste immediately after use in a water-filled, closed, metal container.

**STORAGE:** Pour unused product into smaller containers or add clean glass marbles into the opened container to raise the liquid level.

**VEHICLE TYPE:** Alkyd Fortified, Natural Oils

**WEIGHT PER GALLON:** 7.0 pounds per gallon.

**% SOLIDS:** 30 tby volume.

**FLASH:** 107°F

**V.O.C.:** Maximum 550 grams per liter.

**Daly's Wood Finishing Products**

4522 S 133rd St, Tukwila, WA 98168

[www.dalyswoodfinishes.com](http://www.dalyswoodfinishes.com)

phone(206) 244-8844

toll free(800) 727-9694

fax(206) 246-7691