



## Wood Finishing Products

# Booster Stain Remover™

Product: 17200

08/06/03

### SPECIFICATION SHEET

**DESCRIPTION:** Daly's **Booster Stain Remover** removes imbedded stains from wood, including weather and water marks.

**RECOMMENDED USES:** Daly's **Booster Stain Remover** is designed to be used AFTER all surface coatings have been removed with paint and varnish remover. It may discolor the surface, thus requiring the use of Daly's "A" AND "B" BLEACHING SOLUTIONS afterward. Daly's **Booster Stain Remover** is not intended as a "spot" remover, so be sure to treat the entire surface.

**RECOMMENDED SYSTEMS:** OPEN-GRAINED WOOD (Oak, Mahogany, Walnut): Apply a liberal coat of Daly's **Booster Stain Remover** with a nylon brush. Using a brass wire brush, scrub with the grain until the stain begins to bleed from the wood. Keep wood surface wet with **Booster** at all times while scrubbing. In the case of dark stains, two or three applications are sometimes necessary.

Wash with a sponge damp with water. Sponge two or three times or until very little stain comes off on the sponge. Allow 4 hours drying time.

CLOSE-GRAINED WOOD (Birch, Alder, Fir, Beech): Apply a liberal coat of Daly's **Booster Stain Remover** with a nylon brush. Scrub with #1 steelwool, or 3M pad, working with the grain.

Wash with a sponge damp with water. Sponge two or three times or until very little stain comes off on the sponge. Allow 4 hours drying time.

If the wood is a satisfactory color after using Daly's **Booster Stain Remover** no bleaching will be necessary. If the wood requires lightening, use Daly's "A" AND "B" BLEACHING SOLUTION, making sure to follow all directions on containers for bleaching.

**CLEAN UP:** Water.

**WEIGHT:** 8.8 pounds per gallon.

**FLASH:** Non-flammable.

**V.O.C.:** None.

**CAUTION:** KEEP OUT OF REACH OF CHILDREN.

**CORROSIVE! (CONTAINS SODIUM METALSILICATE AND SODIUM HYDROXIDE)**

Product is caustic. Repeated contact may cause burns. Wear protective clothing, rubber or plastic gloves and eye protection. In the event of skin or eye contact, wash repeatedly with water. If irritation persists seek medical aid.

**REGULATORY:** Request Material Safety Data Sheet for information pertinent to EPA SARA Title III Section 313 Supplier Notification.

## Daly's Wood Finishing Products

3525 Stone Way N, Seattle, WA 98103

phone(206) 633-4200

toll free(800) 735-7019

fax(206)632-2565

S-Booster.pm6-p1/1