



## Wood Finishing Products

# GlosThane™

Product: 14600

08/06/03

### SPECIFICATION SHEET

<b>DESCRIPTION:</b>	Daly's <b>GlosThane</b> is a clear, non-toxic, protective finish extremely resistant to marring, scuffing, alcohol, boiling water and normal cleaning agents.
<b>RECOMMENDED USES:</b>	Interior and exterior surfaces such as doors, paneling, furniture, cabinets, patio furniture, floors, trim and toys. While <b>GlosThane</b> may be applied over most stains, it is suggested to test for compatibility prior to finishing. <b>GlosThane</b> may be applied over Daly's WOOD STAIN, BENITE, BENMATTE AND PASTE WOOD FILLER.
<b>RECOMMENDED SYSTEMS:</b>	Be sure surface is dry and free of sanding dust, dirt, grease, wax or traces of paint and varnish remover. If applied over stain, be sure stain is completely dry. May be applied by brush, roller or spray. Apply as it comes from the can. <b>New or Stained Wood</b> - On unstained wood, a pre-conditioner such as Daly's BENITE may be applied prior to first coat. On stained surfaces follow directions on stain prior to first coat. Second Coat - Sand surface with 220 or finer grit sandpaper to remove imperfections and to rough for good adhesion prior to second coat. If a third coat is desired repeat procedure for second coat. For exterior surfaces, three coats are recommended. <b>Old Work</b> - Make sure surfaces are properly prepared, sanded, cleaned; then apply as for new work. Not recommended for use over shellac and lacquer sanding sealer. When using <b>GlosThane</b> over paste wood fillers other than Daly's, testing should be done first to insure proper adhesion.
<b>COLORS &amp; TINTING:</b>	Not intended to be tinted. If a stain is desired, see instructions for the use of Daly's WOOD STAIN.
<b>THINNING:</b>	Not recommended. Product is ready to use as packaged.
<b>CLEAN UP:</b>	Paint thinner (mineral spirits).
<b>COVERAGE:</b>	400-600 sq. ft. per gallon.
<b>DRY TIME:</b>	Dust free 30 minutes. Recoat 6-8 hours. Ready to use 24 hours. Drying may vary due to weather conditions, air circulation and temperature.
<b>CAUTIONS:</b>	<b>CONTAINS PETROLEUM DISTILLATE: VAPOR HARMFUL. MAY AFFECT THE BRAIN OR NERVOUS SYSTEM CAUSING DIZZINESS, HEADACHE OR NAUSEA. CAUSES EYE, SKIN, NOSE AND THROAT IRRITATION.</b> <b>Notice:</b> Reports have associated repeated and prolonged occupational over exposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. <b>PRECAUTIONS:</b> Keep away from heat and flame. Prevent build-up of vapors by opening windows and doors to achieve cross ventilation. USE ONLY WITH ADEQUATE VENTILATION. Do not breathe vapors or spray mist. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness, or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during and after application. Follow respirator manufacturer's directions for respirator use.

**CAUTIONS (cont'd):** Avoid contact with eyes, skin and clothing. Wash thoroughly after handling.

**SPECIAL INSTRUCTIONS:** **First Aid:** If swallowed, do not induce vomiting. Call physician immediately. If you experience difficulty breathing, leave area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention; for skin, wash thoroughly with soap and water.

**If spilled:** Contain spilled materials and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

To avoid spontaneous combustion during temporary storage, soak soiled rags and waste immediately after use in a water-filled, closed, metal container.

**VEHICLE TYPE:** Uralkyd.

**WEIGHT PER GAL:** 7.4 pounds per gallon

**% SOLIDS:** 43% by volume

**FLASH:** 107°F, Setflash Closed Cup

**V.O.C.:** Maximum 450 grams per liter.

## Daly's Wood Finishing Products

3525 Stone Way N, Seattle, WA 98103

phone(206) 633-4200

toll free(800) 735-7019

fax(206)632-2565