



Wood Finishing Products

LemOil™

Product: 14200

08/06/03

SPECIFICATION SHEET

DESCRIPTION:	Daly's LemOil is an ideal wipe-on treatment designed to clean and maintain all wood surfaces.
RECOMMENDED USES:	Daly's LemOil may be used to clean and maintain paneling, furniture or cabinets which have been oiled, varnished, lacquered or enameled. It is also great on hardwood floors to restore luster to worn areas, leaving a non-slip finish. Excellent for use on previously waxed surfaces.
RECOMMENDED SYSTEMS:	Dampen a soft cloth with LemOil . Apply evenly to surface. Allow to set a few minutes then buff dry using a dry, soft cloth, rubbing briskly with the grain. For heavily soiled areas, apply generously, let set a few minutes, then wipe dry. Repeat if necessary.
APPLICATION:	Lint-free cloth.
THINNING:	Do not thin.
CAUTIONS:	<p>CONTAINS PETROLEUM DISTILLATE: VAPOR HARMFUL. MAY AFFECT THE BRAIN OR NERVOUS SYSTEM CAUSING DIZZINESS, HEADACHE OR NAUSEA. CAUSES EYE, SKIN, NOSE AND THROAT IRRITATION.</p> <p>Notice: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.</p> <p>PRECAUTIONS: Keep away from heat and flame. Prevent build-up of vapors by opening windows and doors to achieve cross ventilation.</p> <p>USE ONLY WITH ADEQUATE VENTILATION. Do not breathe vapors or spray mist. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness, or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during and after application. Follow respirator manufacturer's directions for respirator use. Avoid contact with eyes, skin and clothing. Wash thoroughly after handling.</p> <p>First Aid: If swallowed, do not induce vomiting. Call physician immediately. If you experience difficulty breathing, leave area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention; for skin, wash thoroughly with soap and water.</p> <p>If spilled, contain spilled materials and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.</p> <p>KEEP OUT OF REACH OF CHILDREN</p>
SPECIAL INSTRUCTIONS:	<p>DISPOSAL OF OILY RAGS: To avoid spontaneous combustion during temporary storage, soak soiled rags and waste immediately after use in a water-filled, closed, metal container. STIR WELL before and during use.</p>

% SOLIDS: 6% by volume

VISCOSITY: Not applicable.

WEIGHT PER GAL: 6.6 lb.

VEHICLE TYPE: Oil of Citronella & Tung oil.

FLASH: 103°F

V.O.C.: N/A

Daly's Wood Finishing Products

3525 Stone Way N, Seattle, WA 98103

phone(206) 633-4200

toll free(800) 735-7019

fax(206)632-2565