



## Wood Finishing Products

# Wallpaper Removal Solution

Product: 17900

08/05/03

### SPECIFICATION SHEET

**DESCRIPTION:** Daly's **Wallpaper Removal Solution** is the only stripper you'll need to remove old and unwanted wallcoverings. Daly's **Wallpaper Removal Solution** is concentrated, effective and easy to apply. It will not interfere with application of future wallcoverings. Clean-up is simple.

**RECOMMENDED USES:** Use Daly's **Wallpaper Removal Solution** to do just what the name says: remove wallpaper. **Wallpaper Removal Solution** can be used to strip vinyl-covered and painted wallpaper as well.

**RECOMMENDED SYSTEMS:** Use a drop cloth over carpeting, plants and furniture. Score wallcovering to allow solution to reach the paste. Peelable wallcoverings must be separated from backing prior to scoring.

1. Add 1 quart of **Wallpaper Removal Solution** to 3 gallons of hot (minimum 120°F) water in a clean, plastic pail or bucket.
2. Coat wallcoverings generously with the diluted **Wallpaper Removal Solution** using a sponge, synthetic brush, or pump sprayer.
3. Let sit 10-15 minutes.
4. Repeat steps 2 & 3.

Begin to remove paper using a 4-inch paint scraper. The wallcovering will peel away from the wall in large strips. The scraper is used to ease the paper from the wall. Re-wet sections as you move across the surface. When completed, wash the wall with fresh solution, and rinse with warm water. Let dry completely before redecorating. Work in a well-ventilated area. Gloves are suggested. Avoid spills on carpet and furniture.

**CLEAN UP:** Clean tools with warm water and soap. Remove all spills from furniture and floors immediately. May discolor fabrics on contact.

**COVERAGE:** One gallon of properly diluted **Wallpaper Removal Solution** will remove approximately 400 square feet of wallpaper.

**FLASH:** Daly's **Wallpaper Removal Solution** is water-based, is non-flammable, has no flash point.

**V.O.C.:** Although **Wallpaper Removal Solution** is water-based, it does contain some non-toxic solvent, therefore the Maximum Volatile Organic Compound <350 grams/liter.

**CAUTIONS:** **WARNING! VAPOR CAN BE HARMFUL.**

Use with adequate ventilation. Do not take internally. Wear proper protective equipment such as goggles, plastic or rubber gloves. Close container after each use. Never mix with other chemicals, cleaners, or detergents.

**KEEP OUT OF REACH OF CHILDREN.**

**First Aid:** If swallowed, and gastrointestinal irritation develops, DO NOT INDUCE VOMITING. Give water or milk to drink, to dilute solution, and get medical attention.

Eye contact: Flush eyes immediately with water. If irritation persists, get medical attention.

Inhalation: If a person is overcome from vapors while spraying, remove individual to fresh air. If effects persist, get medical attention.

Skin contact: If irritation develops, wash area thoroughly with soap and water.

**CAUTIONS(cont'd):** When applying and rinsing solution, surfaces such as ladders, scaffolding and walking areas may become slippery. Rinse thoroughly to remove from such surfaces.  
**DO NOT FREEZE.**  
However, if product is frozen, allow to thaw at room temperature; do not force-thaw.

**Daly's Wood Finishing Products**

3525 Stone Way N, Seattle, WA 98103

phone(206) 633-4200

toll free(800) 735-7019

fax(206)632-2565

S-RemovalSol.pm6-p2/2