



Wood Finishing Products

SeaFin™ Sealer Filler Stain

Product: 15300

08/06/03

SPECIFICATION SHEET

DESCRIPTION:	Daly's SeaFin Marine Sealer Filler Stain is a finely ground sealer filler stain for use on open-grained woods when filling and staining are required. Ready to apply, it packs the pores of open grained woods, stains when a richer color is desired, and seals to create a better base for applying a Spar Varnish or polyurethane finish.
RECOMMENDED USES:	For use on marine and exterior surfaces prior to the application of Daly's SEAFIN SUPER SPAR GLOSS VARNISH, or other finishing product.
RECOMMENDED SYSTEMS:	Apply as it comes from container with a brush. Apply first <i>WITH</i> the grain, then working in <i>CROSS</i> grain. Allow 15 to 20 minutes drying time, or until dull. Work filler stain into grain with a coarse rag or burlap to remove excess, followed by wiping with soft absorbent rag to remove cloudiness and to attain desired stain shade.
THINNING:	If required, paint thinner.
CLEAN UP:	Paint thinner (Mineral spirits).
COVERAGE:	400-500 sq.ft. per gallon.
DRY TIME:	Allow to dry 12 to 24 hours before applying finish. NOTE: Weather conditions will vary drying time. Do not apply before morning dew has dried and stop well before dusk.
CAUTIONS:	CONTAINS PETROLEUM DISTILLATE: VAPOR HARMFUL. MAY AFFECT THE BRAIN OR NERVOUS SYSTEM CAUSING DIZZINESS, HEADACHE OR NAUSEA. CAUSES EYE, SKIN, NOSE AND THROAT IRRITATION. Notice: Reports have associated repeated and prolonged occupational over exposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. PRECAUTIONS: Keep away from heat and flame. Prevent build-up of vapors by opening windows and doors to achieve cross ventilation. USE ONLY WITH ADEQUATE VENTILATION. Do not breathe vapors or spray mist. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness, or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during and after application. Follow respirator manufacturer's directions for respirator use. Avoid contact with eyes, skin and clothing. Wash thoroughly after handling. First Aid: If swallowed, do not induce vomiting. Call physician immediately. If you experience difficulty breathing, leave area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention; for skin, wash thoroughly with soap and water.

SPECIAL INSTRUCTIONS: **If spilled:** Contain spilled materials and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.
To avoid spontaneous combustion during temporary storage, soak soiled rags and waste immediately after use in a water-filled, closed, metal container.
DISPOSAL OF OILY RAGS: To avoid spontaneous combustion during temporary storage, soak soiled rags and waste immediately after use in a water-filled, closed container.
STORAGE: **SeaFin Sealer Filler Stain** will remain in good condition in the original unopened container for a period of years. Once opened **SeaFin Sealer Filler Stain** should not be stored in a partially full container.

WEIGHT PER GAL: 10.3-10.4 lb.
VEHICLE TYPE: Vegetable Oil/Phenolic.
% SOLIDS: 64% - volume
V.O.C.: Maximum 285 grams per liter.
FLASH: 107°F Seta Flash Closed Cup

Daly's Wood Finishing Products

3525 Stone Way N, Seattle, WA 98103

phone(206) 633-4200

toll free(800) 735-7019

fax(206)632-2565