



Wood Finishing Products

SeaFin™ Teak Cleaner

Product: 1574

08/06/03

SPECIFICATION SHEET

DESCRIPTION:	Daly's SeaFin Teak Cleaner is a one-part cleaner for restoring weathered teak, prior to applying a new finish.
RECOMMENDED USES:	Daly's SeaFin Teak Cleaner is for use on exterior teak decks, brightwork and railings.
RECOMMENDED SYSTEMS:	Dilute one part SeaFin Teak Cleaner with two parts water in a plastic container. Apply diluted solution using synthetic bristle or fiber scrub brush. Allow to set for 3-5 minutes. Then, scrub with grain of wood using stiff fiber scrub brush. Rinse thoroughly with fresh water. Let dry and repeat if necessary. To bring out the natural wood color, use Daly's OXALIC ACID. Mix as per instructions. Apply with a synthetic bristle brush, let set for 5 minutes, but do not let it dry. Rinse with fresh water. After teak has been restored and is dry, sand and apply one of Daly's SEAFIN Finishes.
COVERAGE:	3 quarts of mix will cover approximately 150 sq. ft.
CAUTION:	CORROSIVE! Harmful or fatal if swallowed. Irritant to eyes and skin. Do not take internally. Wear proper protective clothing such as goggles, rubber or plastic gloves. Close container after each use. NEVER MIX WITH OTHER CHEMICALS, CLEANERS OR DETERGENTS as mixture may release harmful gases. KEEP OUT OF REACH OF CHILDREN.
FIRST AID:	If swallowed, call physician immediately. DO NOT INDUCE VOMITING. Give water or milk to drink. Eye contact: Flush eyes immediately with water for 15 minutes. If irritation persists, seek medical aid. Skin contact: Wash thoroughly with soap and water. If irritation persists, seek medical aid.
CLEAN UP:	Clean tools and equipment with water. Surfaces such as ladders and walk-ways may become slippery, therefore, rinse with water immediately to avoid safety hazards
FLASH:	Non-flammable.
V.O.C.:	None.
SPECIAL INSTRUCTIONS:	DO NOT FREEZE. However, if product is frozen, allow to thaw at room temperature; do not force thaw. SeaFin Teak Cleaner is not a paint remover. For problem areas, a stronger solution may be mixed by using 1 part SeaFin Teak Cleaner to 1 part water, then follow directions. SeaFin Teak Cleaner may be applied to damp surfaces, but not to a wet surface. For removing discoloration, rust stains and to make old wood look new, use Daly's OXALIC ACID. For refinishing, use Daly's SEAFIN products. Always test on a small, hidden area first, to be sure of desired results. If splashed on surfaces other than wood, rinse immediately with water.
REGULATORY:	This product contains chemicals subject to EPA SARA Title III Section 313 Supplier Notification. Request Material Safety Data Sheet for pertinent information.

Daly's Wood Finishing Products

3525 Stone Way N, Seattle, WA 98103

phone(206) 633-4200

toll free(800) 735-7019

fax(206)632-2565

S-SteakCleaner.pm6-p1/1