



Wood Finishing Products
A Division of Farwest Paint Mfg. Co.

SPECIFICATION SHEET

SatinThane™

Product:14700

7/2017

DESCRIPTION:

Daly's **SatinThane** is a clear, non-toxic, protective finish extremely resistant to marring, scuffing, alcohol, boiling water and normal cleaning agents.

RECOMMENDED USES:

Interior and exterior surfaces such as doors, paneling, furniture, cabinets, patio furniture, floors, trim and toys. While **SatinThane** may be applied over most stains, it is suggested to test for compatibility prior to finishing. **SatinThane** may be applied over Daly's Wood Stain, Benite and BenMatte.

RECOMMENDED SYSTEMS:

Be sure surface is dry and free of sanding dust, dirt, grease, wax or traces of paint and varnish remover. If applied over stain, be sure stain is completely dry. May be applied by brush, roller or spray. Apply as it comes from the can.

NEW OR STAINED WOOD: On unstained wood, a pre-conditioner such as Daly's BENITE may be applied prior to first coat. On stained surfaces follow directions on stain prior to first coat. Second Coat - Sand surface with 220 or finer grit sandpaper to remove imperfections and to rough for good adhesion prior to second coat. If a third coat is desired repeat procedure for second coat. For exterior surfaces, three coats are recommended.

OLD WORK: Make sure surfaces are properly prepared, sanded, cleaned; then apply as for new work. Not recommended for use over shellac and lacquer sanding sealer. When using **SatinThane** over paste wood fillers testing should be done first to insure proper adhesion.

COLORS & TINTING:

Not intended to be tinted. If a stain is desired, see instructions for the use of Daly's WOOD STAIN.

THINNING: Not recommended. Product is ready to use as packaged.

CLEAN UP: Paint thinner (Mineral spirits).

COVERAGE: 400 to 600 square feet per gallon

DRY TIME:

Dust free 30 minutes. Recoat 6-8 hours. Ready to use 24 hours. Drying may vary due to weather conditions, air circulation and temperature.

CAUTIONS:

CONTAINS PETROLEUM DISTILLATE: VAPOR HARMFUL. MAY AFFECT THE BRAIN OR NERVOUS SYSTEM CAUSING DIZZINESS, HEADACHE OR NAUSEA. CAUSES EYE, SKIN, NOSE AND THROAT IRRITATION. Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

CAUTIONS CONTINUED:

PRECAUTIONS: Keep away from heat and flame. Prevent build-up of vapors by opening windows and doors to achieve cross ventilation.

USE ONLY WITH ADEQUATE VENTILATION. Do not breathe vapors or spray mist. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness, or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during and after application. Follow respirator manufacturer's directions for respirator use. Avoid contact with eyes, skin and clothing. Wash thoroughly after handling. Close container after each use.

Warning: Rags and other waste materials soiled with this product may spontaneously catch fire if improperly discarded. Soak soiled rags and waste immediately after use in a water-filled, closed metal container. For disposal guidance of unused materials, contact a house hold hazardous waste program or your local or state government environmental control agency.

First Aid: If swallowed, do not induce vomiting. Call physician immediately. If you experience difficulty breathing, leave area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention. For skin contact, wash thoroughly with soap and water.

SPECIAL INSTRUCTIONS:

IF SPILLED: Contain spilled materials and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

DISPOSAL OF OILY RAGS: To avoid spontaneous combustion during temporary storage, soak soiled rags and waste immediately after use in a water-filled, closed, metal container.

STORAGE: Pour unused product into smaller containers or add clean glass marbles into the opened container to raise the liquid level.

VEHICLE TYPE: Uralkyd

WEIGHT PER GALLON: 7.5 pounds per gallon.

% SOLIDS: 43% by volume.

FLASH: 107°F Seaflash Closed Cup

V.O.C.: Maximum 450 grams per liter.

Daly's Wood Finishing Products

4522 S 133rd St, Tukwila, WA 98168

www.dalyswoodfinishes.com

phone(206) 244-8844

toll free(800) 727-9694

fax(206) 246-7691