



SPECIFICATION SHEET

Semi-Transparent Exterior Stain

Product:16200

11/2018

DESCRIPTION:

Daly's **Semi-Transparent Exterior Stain** is formulated for use on either smooth or rough wood exterior surfaces, and is especially useful as a treatment over older, weathered, transparent and semi-transparent stains without "total hide" of the full bodied stains.

RECOMMENDED USES:

Daly's **Semi-Transparent Exterior Stain** gives a distinctive low luster that provides protection to any exposed surfaces such as siding, railings, beams and other surfaces. It is designed for use on exterior surfaces that will not be further treated.

RECOMMENDED SYSTEMS:

NEW WORK: One coat of **Semi-Transparent Exterior Stain** is usually sufficient. Two coats will give added protection.

OLD WORK: Previously stained surfaces in the same color range can be restored with one coat of Daly's **Semi-Transparent Exterior Stain**.

COLORS & TINTING:

Available in a wide range of colors. It may be tinted with up to 6 ounces per gallon of universal pigments or colorants ground in oil. Always test first for compatability.

THINNING: Do not thin.

CLEAN UP: Paint thinner (Mineral spirits).

COVERAGE: Approximately 150 to 400 sq.ft. per gallon depending on surface texture and dryness.

APPLICATION: Brush, roller or spray.

DRY TIME: 2-6 hours dry to touch. 12-24 hours to recoat depending on conditions.

CAUTIONS:

CONTAINS PETROLEUM DISTILLATE: VAPOR HARMFUL. MAY AFFECT THE BRAIN OR NERVOUS SYSTEM CAUSING DIZZINESS, HEADACHE OR NAUSEA. CAUSES EYE, SKIN, NOSE AND THROAT IRRITATION. Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

PRECAUTIONS: Keep away from heat and flame. Prevent build-up of vapors by opening windows and doors to achieve cross ventilation.

USE ONLY WITH ADEQUATE VENTILATION. Do not breathe vapors or spray mist. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness, or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during and after application. Follow respirator manufacturer's directions for respirator use. Avoid contact with eyes, skin and clothing. Wash thoroughly after handling. Close container after each use.

CAUTIONS CONTINUED:

First Aid: If swallowed, do not induce vomiting. Call physician immediately. If you experience difficulty breathing, leave area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention. For skin contact, wash thoroughly with soap and water.

KEEP OUT OF REACH OF CHILDREN. Made with non-photochemically reactive solvents.

SPECIAL INSTRUCTIONS:

IF SPILLED: Contain spilled materials and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

DISPOSAL OF OILY RAGS: To avoid spontaneous combustion during temporary storage, soak soiled rags and waste immediately after use in a water-filled, closed, metal container.

VEHICLE TYPE: Resin, oils.

PIGMENT TYPE: Oil pigment type.

WEIGHT PER GALLON: 7 to 8 pounds per gallon

% SOLIDS: 31% to 32% by volume

FLASH: 102°F

V.O.C.: Maximum 550 grams per liter.

FLASH: 15 seconds #2 Zahn Cup.

REGULATORY: Request Safety Data Sheet for pertinent information.

Daly's Wood Finishing Products

4522 S 133rd St, Tukwila, WA 98168

www.dalyswoodfinishes.com

phone(206) 244-8844

toll free(800) 727-9694

fax(206) 246-7691