



Wood Finishing Products

Semi-Transparent Exterior Stain

Product: 16200

08/06/03

SPECIFICATION SHEET

DESCRIPTION:	Daly's Semi-Transparent Exterior Stain is formulated for use on either smooth or rough wood exterior surfaces, and is especially useful as a treatment over older, weathered transparent and semi-transparent stains without "total hide" of the full bodied stains.
RECOMMENDED USES:	Daly's Semi-Transparent Exterior Stain gives a distinctive low luster that provides protection to any exposed surfaces such as siding, railings, beams and other surfaces. It is designed for use on exterior surfaces that will not be further treated.
RECOMMENDED SYSTEMS:	NEW WORK: One coat of Semi-Transparent Exterior Stain is usually sufficient. Two coats will give added protection. OLD WORK: Previously stained surfaces in the same color range can be restored with one coat of Daly's Semi-Transparent Exterior Stain .
COLORS & TINTING:	Available in a wide range of colors. It may be tinted with up to 6 ounces per gallon of universal pigments. Always test first for compatibility and desired shade.
THINNING:	Do not thin.
CLEAN UP:	Paint thinner (Mineral spirits).
COVERAGE:	150 to 400 sq.ft. per gallon depending on surface texture and dryness.
APPLICATION:	Brush, roller or spray.
DRY TIME:	2-6 hours dry to touch. 12-24 hours to recoat depending on conditions.
CAUTIONS:	CONTAINS PETROLEUM DISTILLATE: VAPOR HARMFUL. MAY AFFECT THE BRAIN OR NERVOUS SYSTEM CAUSING DIZZINESS, HEADACHE OR NAUSEA. CAUSES EYE, SKIN, NOSE AND THROAT IRRITATION. Notice: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. PRECAUTIONS: Keep away from heat and flame. Prevent build-up of vapors by opening windows and doors to achieve cross ventilation. USE ONLY WITH ADEQUATE VENTILATION. Do not breathe vapors or spray mist. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness, or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during and after application. Follow respirator manufacturer's directions for respirator use. Avoid contact with eyes, skin and clothing. Wash thoroughly after handling. First Aid: If swallowed, do not induce vomiting. Call physician immediately. If you experience difficulty breathing, leave area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention; for skin, wash thoroughly with soap and water.

CAUTIONS(continued): **If spilled**, contain spilled materials and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.
Made with non-photochemically reactive solvents.
KEEP OUT OF REACH OF CHILDREN

SPECIAL INSTRUCTIONS: **DISPOSAL OF OILY RAGS:** To avoid spontaneous combustion during temporary storage, soak soiled rags and waste immediately after use in a water-filled, closed, metal container. **STIR WELL** before and during use.

VEHICLE TYPE: Resin, oils.

PIGMENT TYPE: Oil pigment type.

WEIGHT PER GAL: 7-8 lb.

% SOLIDS: 31-32% - volume

FLASH: 102°F

V.O.C.: Maximum 550 grams per liter.

REGULATORY: This product contains a chemical subject to EPA SARA Title III Section 313 Supplier Notification. Request Material Safety Data Sheet for pertinent information.

Daly's Wood Finishing Products

3525 Stone Way N, Seattle, WA 98103

phone(206) 633-4200

toll free(800) 735-7019

fax(206)632-2565